

Package: docopt (via r-universe)

June 15, 2024

Type Package

Title Command-Line Interface Specification Language

Version 0.7.1

Author Edwin de Jonge (edwindjonge@gmail.com)

Maintainer Edwin de Jonge <edwindjonge@gmail.com>

Description Define a command-line interface by just giving it a description in the specific format.

License MIT + file LICENSE

URL <https://github.com/docopt/docopt.R>

BugReports <https://github.com/docopt/docopt.R/issues>

Imports methods

Suggests testthat

RoxygenNote 7.1.0

Repository <https://docopt.r-universe.dev>

RemoteUrl <https://github.com/docopt/docopt.r>

RemoteRef HEAD

RemoteSha ebdeb31d911584eab409799423edce3e48a85a2c

Contents

docopt-package	2
docopt	2
Index	4

docopt-package *Docopt command line specification*

Description

docopt helps you to define an interface for your command-line app, and automatically generate a parser for it.

Details

For more information see <http://docopt.org>

docopt *Parse args based on command-line interface described in doc.*

Description

docopt creates your command-line interface based on its description that you pass as doc. Such description can contain `-options`, `<positional-argument>`, commands, which could be [optional], (required), (mutually | exclusive) or repeated...

Usage

```
docopt(
  doc,
  args = commandArgs(TRUE),
  name = NULL,
  help = TRUE,
  version = NULL,
  strict = FALSE,
  strip_names = !strict,
  quoted_args = !strict
)
```

Arguments

doc	character vector with command line specification
args	character vector of commandline arguments. If args is missing <code>commandArgs(trailingOnly=TRUE)</code> will be used.
name	Currently not used
help	logical should "-h" or "--help" generate a usage string?
version	character. If supplied the option "-v" generates the given version number and stops.

<code>strict</code>	logical if TRUE docopt will conform to docopt.py in and output (<code>strip_names=FALSE</code> and <code>quoted_args=FALSE</code>)
<code>strip_names</code>	if TRUE it will remove dashes and angles from the resulting names and add these to the resulting list. Note that this is different from docopt standard!
<code>quoted_args</code>	if TRUE it will accept quoted arguments. Note that this is different from docopt standard!

Value

named list with all parsed options, arguments and commands.

References

<http://docopt.org>,

Examples

```
"Usage: my_program.R [-hso FILE] [--quiet | --verbose] [INPUT ...]
-h --help      show this
-s --sorted    sorted output
-o FILE        specify output file [default: ./test.txt]
--quiet        print less text
--verbose      print more text" -> doc
docopt(doc, "-s --quiet")
```

Index

`docopt`, [2](#)

`docopt-package`, [2](#)